

SAFETY DATA SHEET

In accordance with 1907/2006 annex II and 1272/2008
(All references to EU regulations and directives are abbreviated into only the numeric term)
Issued 2023-05-30
Version number 1.0



HOZON FINISHES

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name Nano Top Coat
UFI: H300-U0UE-0002-85FE

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Surface treatment of wood

1.3. Details of the supplier of the safety data sheet

Company Hozon Trading Co. AB
Tryvägen 29
51335 Fristad
Sweden
Telephone +46 (0) 735126263
E-mail hozonfinishes@gmail.com

1.4. Emergency telephone number

Phone number for emergencies: 999 or 112. The numbers are available 24/7.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Flam. Liq. 3, H226
Asp. tox. 1, H304
(See section 16)

2.2. Label elements

Hazard pictogram



Signal word Danger

Hazard statements
H226 Flammable liquid and vapour
H304 May be fatal if swallowed and enters airways

Precautionary statements
P101 If medical advice is needed, have product container or label at hand
P102 Keep out of reach of children
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER
P331 Do NOT induce vomiting
P405 Store locked up
P501 Dispose of contents and container to authorised waste disposal facility

Supplemental hazard information

Contains: DISTILLATES (PETROLEUM), HYDRO- TREATED LIGHT

2.3. Other hazards

This product does not contain any substances that are assessed to be a PBT or a vPvB

The product does not contain any substances identified as having endocrine disruptive properties in accordance with the criteria set out in (EU) 2017/2100 or (EU) 2018/605.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Note that the table shows known hazards of the ingredients in pure form. These hazards are reduced or eliminated when mixed or diluted, see Section 16d.

| Constituent | Classification | Concentration |
|--|---------------------------------------|---------------|
| DISTILLATES (PETROLEUM), HYDRO- TREATED LIGHT | | |
| CAS No: 64742-47-8 EC No: 265-149-8 Index No: 649-422-00-2 | Flam. Liq. 3, Asp. tox. 1; H226, H304 | >85 % |

Explanations to the classification and labelling of the ingredients are given in Section 16e. Official abbreviations are printed in normal font. Text in italics are specifications and/or complements used in the calculation of the classification of this mixture, see Section 16b.

SECTION 4: First aid measures

4.1. Description of first aid measures

Generally

In case of concern, or if symptoms occur, call a doctor/physician.

Upon breathing in

Bring the injured person out into fresh air. Give artificial respiration if breathing has stopped. If breathing is difficult let trained personnel administer oxygen. Let the injured person rest in a warm place with fresh air and seek medical advice immediately.

Upon eye contact

Rinse the eye for several minutes with lukewarm water. If irritation persists call a doctor.
Remove contact lenses immediately if possible.

Upon skin contact

Remove contaminated clothing.
Wash the skin with soap and water.
If symptoms occur, contact a physician.

Upon ingestion

Rinse mouth out thoroughly first with water, then SPIT OUT the rinse water. Drink at least half a litre of water and seek medical advice. DO NOT INDUCE VOMITING.

4.2. Most important symptoms and effects, both acute and delayed

Upon breathing in

May be fatal if swallowed and enters airways.
Irritation may occur.

Upon eye contact

Transient eye irritation.

Upon ingestion

Indisposition and vomiting if swallowed.
Risk of aspiration, resulting in chemical pneumonitis.

4.3. Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

Upon contact with a doctor, make sure to have the label or this safety data sheet with you.

Symptoms of poisoning may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Recommended extinguishing agents

Extinguish with water mist, powder, carbon dioxide or alcoholresistant foam.

Unsuitable extinguishing agents

May not be extinguished with water dispersed under high pressure.

5.2. Special hazards arising from the substance or mixture

Emits flammable vapours which may form an explosive mixture with air.

Produces fumes containing harmful gases (carbon monoxide and carbon dioxide) when burning, and, in case of incomplete combustion, aldehydes and other toxic, harmful, irritant or environmentally harmful substances.

In case of fire, high pressure may build up causing the packaging to explode.

5.3. Advice for firefighters

Protective measures should be taken regarding other material at the site of the fire.

In case of fire use proper breathing apparatus.

Wear full protective clothing.

Cool closed containers that were exposed to fire with water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Note the risk of ignition.

Switch off equipment which has an exposed flame, glows, or has a heat source of some other kind.

Switch off power at the main switch. Do not use the power switch in the room where the spillage has occurred.

Note, risk for formation of sparks due to static electricity. Do not remove clothing in a room where spillage has occurred.

Evacuate the accident area and call an ambulance, if relevant.

Keep unauthorized and unprotected people at a safe distance.

Do not inhale vapours and avoid contact with skin, eyes and clothes when cleaning up the spillage.

Ensure good ventilation.

Use recommended safety equipment, see section 8.

Use breathing apparatus when oxygen levels are low or unknown.

6.2. Environmental precautions

Avoid release to drains, soil or watercourses.

Prevent from entering sewers, basements and pits, or any place where gas accumulation could be dangerous.

Notify rescue services for larger spillage.

6.3. Methods and material for containment and cleaning up

Do NOT use tools emitting sparks when cleaning.

Absorb the liquid with an inert absorbent, vermiculite, for example. Collect the material for disposal at a waste disposal facility.

Residues left behind after cleaning shall be treated as hazardous waste. For further information, contact the local authority sanitisation works. Present this safety data sheet.

Rinse area thoroughly with water.

Ensure good ventilation after sanitation.

6.4. Reference to other sections

See section 8 and 13 for personal protection equipment and disposal considerations.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Take the necessary preventive and protective measures for safe handling.

Open fire, hot items, sparks or other ignition sources must not be present in the environment used for handling this product.

Store this product separately from food items and keep it out of the reach of children and pets.

The product may be electrostatically charged. Always ground the containers while transferring the contents from one container to another. Do not use tools that may cause sparks.

Do not inhale the fumes and avoid exposure to skin, eyes and clothing.

Work in order to avoid spillage. If spillage does occur, address it immediately in accordance with the directions specified in Section 6 of this safety data sheet.

Do not eat, drink or smoke in premises where this product is handled.

Remove contaminated clothing.

Wash contaminated clothing before reuse.

Wash your hands after using the product.

Keep away from incompatible products.

Use recommended safety equipment, see section 8.

Implement appropriate engineering controls if necessary, see Section 8.

7.2. Conditions for safe storage, including any incompatibilities

Take the necessary preventive and protective measures for safe storage.

The product should be stored in a manner which prevents hazards to health and the environment. Avoid exposure to humans and animals and do not discharge the product in a sensitive environment.

Store separately from food and animal fodder, incl. utensils or surfaces which have been in contact with these things.

Keep out of reach for children.

Always use sealed and visibly labeled packages.

Store tightly, in original packaging.

Store as flammable liquid.

Store in a well-ventilated and locked place.

Store in dry and cool area.

Do not store close to incompatible materials (see section 10.5).

7.3. Specific end use(s)

See identified uses in Section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National limit values

All ingredients (cf. Section 3) lack occupational exposure limit values.

DNEL

No data available.

PNEC

No data available.

8.2. Exposure controls

The risks posed by the product or its constituents must be considered in the task specific risk assessment, in accordance with current working environment legislation. The risk assessment should be reviewed regularly and updated if necessary.

8.2.1. Appropriate engineering controls

The ventilation in the workplace must ensure an air quality that meets the requirements of the current working environment legislation. Local exhaust ventilation should be used to remove airborne contaminants at the source.

Emergency showers and eye-rinsing facilities must be available at the workplace.

Eye/face protection

Eye protection should be worn if there is any danger of direct exposure or splashing.

Skin protection

Use suitable protective clothing.

Use protective gloves fulfilling the standard EN374 if there is a risk of direct contact.

During continuous contact use gloves with a minimum breakthrough time of at least 240 minutes, preferably over 480 minutes.

The most suitable protective glove should be chosen in consultation with the glove supplier, taking into account the risk assessment for the specific task and the properties of the chemicals involved. Note that the breakthrough time of the material is affected by the duration of the exposure, temperature conditions, abrasion, etcetera.

Respiratory protection

Use appropriate respiratory protective equipment in case of insufficient ventilation.

The most appropriate respiratory protective equipment should be decided in consultation with the appointed safety representative, taking into account the risk assessment for the specific task.

Based on the physical and chemical properties of the product, the following filter type(s) and/or filter combination(s) are recommended:

– A/P2.

– A/P3.

8.2.3. Environmental exposure controls

For limiting environmental exposure, see section 12.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|--|--------------------------------|
| (a) Physical state | liquid Form: liquid |
| (b) Colour | colourless |
| (c) Odour | characteristic |
| (d) Melting point/freezing point | -25 °C |
| (e) Boiling point or initial boiling point and boiling range | 175 °C |
| (f) Flammability | Not indicated |
| (g) Lower and upper explosion limit | 0.9 - 12 % |
| (h) Flash point | 44 °C |
| (i) Auto-ignition temperature | 275 °C |
| (j) Decomposition temperature | Not indicated |
| (k) pH | Not indicated |
| (l) Kinematic viscosity | 1.063 mm ² /s |
| (m) Solubility | Solubility in water: Insoluble |
| (n) Partition coefficient n-octanol/water (log value) | Not indicated |
| (o) Vapour pressure | 1.33 kPa |
| (p) Density and/or relative density | 0.8 g/cm ³ |
| (q) Relative vapour density | >2.52 |
| (r) Particle characteristics | Not indicated |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Not indicated

9.2.2. Other safety characteristics

(e) evaporation rate 1.4

SECTION 10: Stability and reactivity

10.1. Reactivity

Vapour can create explosive mixtures with air.

10.2. Chemical stability

The product is stable at normal storage and handling conditions.

10.3. Possibility of hazardous reactions

May emit volatile, flammable vapours. Avoid handling close to heat or ignition sources.

10.4. Conditions to avoid

Avoid heat, sparks and open flames.

Protect from heat and direct sunlight.

10.5. Incompatible materials

Avoid contact with:

Peroxides.

Acids.

Oxidising substances.

10.6. Hazardous decomposition products

None under normal conditions.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Information on possible health hazards are based on experience and / or toxicological properties of several components in the product.

If vomiting there is a risk of the product entering the lungs, which subsequently may cause chemical lung inflammation.

Acute toxicity

The product is not classified as acutely toxic.

Skin corrosion/irritation

The product is not classified for skin corrosion/irritation.

Serious eye damage/irritation

The product is not classified as irritant to the eyes.

Respiratory or skin sensitisation

The product is not classified as sensitising.

Germ cell mutagenicity

The product is not classified as mutagen.

Carcinogenicity

The product is not classified as carcinogenic.

Reproductive toxicity

The product is not classified as a reproductive toxicant.

STOT-single exposure

The product is not classified for specific organ toxicity after single exposure.

STOT-repeated exposure

The product is not classified for specific organ toxicity after repeated exposure.

Aspiration hazard

The product may be fatal if swallowed and enters airways.

Monitor aspiration risk if vomiting occurs.

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

The product does not contain any substances identified as having endocrine disruptive properties in accordance with the criteria set out in (EU) 2017/2100 or (EU) 2018/605.

11.2.2. Other information

Not indicated.

SECTION 12: Ecological information

12.1. Toxicity

Prevent release on land, in water and drains.

The product is not to be labelled as an environmental hazard. However, it is not inconceivable that large emissions, or repeated small emissions, can have a harmful effect on the environment.

12.2. Persistence and degradability

The product degrades in the natural environment.

12.3. Bioaccumulative potential

This product or some of its ingredients can possibly accumulate in nature.

12.4. Mobility in soil

Information about mobility in nature is not available.

12.5. Results of PBT and vPvB assessment

This product does not contain any substances that are assessed to be a PBT or a vPvB.

12.6. Endocrine disrupting properties

The product does not contain any substances identified as having endocrine disruptive properties in accordance with the criteria set out in (EU) 2017/2100 or (EU) 2018/605.

12.7. Other adverse effects

Films formed on water may affect oxygen transport and can damage organisms.

Petroleum products can destroy the insulating properties of fur and feathers placing seabirds and marine mammals at risk of freezing to death.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste handling of the product

Avoid discharge into sewers.

Discarded products must be disposed of as hazardous waste in accordance with regulations.

Not completely emptied packaging can contain remnants of dangerous substances and should therefore be handled as hazardous waste according to the above. Completely emptied packaging can be recycled.

See directive 2008/98/EC on waste. Observe national or regional provisions on waste management.

SECTION 14: Transport information

Where not otherwise stated the information applies to all of the UN Model Regulations, i.e. ADR (road), RID (railway), ADN (inland waterways), IMDG (sea), and ICAO (IATA) (air).

14.1. UN number or ID number

1139

14.2. UN proper shipping name

COATING SOLUTION

14.3. Transport hazard class(es)

Class

3: Flammable liquids

Classification code (ADR/RID)

F1: Flammable liquids having a flash-point of or below 60 °C

Subsidiary risk (IMDG)

No subsidiary risk according to IMDG

Labels



14.4. Packing group

Packing group III

14.5. Environmental hazards

Not applicable

14.6. Special precautions for user

Tunnel restrictions

Tunnel category: D/E

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

14.8 Other transport information

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6)

Stowage category not indicated (IMDG)

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

DIRECTIVE 2004/42/CE OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 21 April 2004 on the limitation of emissions of volatile organic compounds due to the use of organic solvents in certain paints and varnishes and vehicle refinishing products and amending Directive 1999/13/EC.

15.2. Chemical safety assessment

Assessment and chemical safety report in accordance with 1907/2006 Annex I has not yet been performed.

SECTION 16: Other information

16a. Indication of where changes have been made to the previous version of the safety data sheet

Revisions of this document

This is the first version

16b. Legend to abbreviations and acronyms used in the safety data sheet

Full texts for Hazard Class and Category Code mentioned in section 3

Flam. Liq. 3 Flammable liquids, Hazard Category 3 - Flam. Liq. 3, H226 - Flammable liquid and vapour

Asp. tox. 1 Aspiration hazard, Hazard Category 1 - Asp. tox. 1, H304 - May be fatal if swallowed and enters airways

Explanations of the abbreviations in Section 14

ADR European Agreement concerning the International Transport of Dangerous Goods by Road

RID Regulations concerning the International Transport of Dangerous Goods by Rail

IMDG International Maritime Dangerous Goods Code

ICAO International Civil Aviation Organization (ICAO, 999 University Street, Montreal, Quebec H3C 5H7, Canada)

IATA The International Air Transport Association

Tunnel restriction code: D/E; Transport by bulk or via tank: Passage forbidden through tunnels of category D and E, Other transportation means: Passage forbidden through tunnels of category E

Transport category: 3; Maximum total quantity per transport unit: 1000 kgs or litres (ADR 1.1.3.6)

16c. Key literature references and sources for data

Sources for data

Primary data for the calculation of the hazards has preferentially been taken from the official European classification list, 1272/2008 Annex I, as updated to 2023-05-30.

Where such data was not available, alternative documentation used to establish the official classification was used, e.g. IUCLID (International Uniform Chemical Information Database). As a second alternative, information was used from reputable international chemical industries, and as a third alternative other available information was used, e.g. material safety data sheets from other suppliers or information from non-profit associations, where reliability of the source was assessed by expert opinion. If, in spite of this, reliable information could not be sourced, the hazards were assessed by expert opinions based on the known hazards of similar substances, and according to the principles in 1907/2006 and 1272/2008.

Full texts for Regulations mentioned in this Safety Data Sheet

1907/2006 REGULATION (EC) No 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC

1272/2008 REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006

2008/98/EC DIRECTIVE 2008/98/EC OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 19 November 2008 on waste and repealing certain Directives

16d. Methods of evaluating information referred to in 1272/2008 Article 9 which was used for the purpose of classification

Hazard calculation for this mixture has been performed as a cumulative assessment with the aid of expert assessments in accordance with 1272/2008 Annex I, where all available information which may be significant to establishing the hazards of the mixture was assessed together, and in accordance with 1907/2006 Annex XI.

16e. List of relevant hazard statements and/or precautionary statements

Full texts for hazard statements mentioned in section 3

H226 Flammable liquid and vapour

H304 May be fatal if swallowed and enters airways

16f. Advice on any training appropriate for workers to ensure protection of human health and the environment

Warning for misuse

Not indicated.

Other relevant information

Not indicated

Editorial information



This material safety data sheet has been prepared and checked by KemRisk®, KemRisk Sweden AB, Platensgatan 8, SE-582 20 Linköping, Sweden, www.kemrisk.se